

Pas Reform SmartHeat™ 2L

For short periods of heat treatment during egg storage





SmartHeat™ 2L

Heat treatment is a tool to reduce the negative effect of long egg storage

Benefits

Heat treatment during egg storage is proven to reduce the negative effect of long egg storage times. It has been shown to improve hatchability and chick quality, even if eggs are only stored for 5-7 days. This positive effect is attributed to the increased number of viable cells produced in the blastoderm by short periods of increased temperature.


How it works SmartHeat™ i

SmartHeat™ is an electrically heated unit, so that it may be easily be placed close to the egg storage room for flexibility and convenience in use.

- Preparation: For each single heat treatment, eggs placed in setter trays on trolleys are moved from the storage room into SmartHeat™ and the program begins. The program runs in 'negative' time mode, i.e. at the end of the set period of heat treatment (which can be set for temperature and time according to local conditions and egg quality), the timer reaches zero
- Preheating + Heat treatment: After a period of preheating at 77°F (to achieve uniform egg temperature before starting heat treatment),
 SmartHeat™ initiates the rise of temperature to achieve uniform eggshell temperature of 90°F
- Cool down: After the required, programmable hours of heat treatment have been administered, SmartHeat™will initiate the required cool down period
- Back to egg storage: At the end of the cooling period, when average eggshell temperature is closer to storage room temperature, the eggs are returned to the storage room
- Repetition: When egg storage time will exceed approx. 14 days, a second and even a third heat treatment is beneficial for optimizing hatchability and preserving chick quality

Related products

- SmartTray™ 150
- SmartTray ™162
- ► Farm trolley
- Setter trolleySmartSetPro™



Technical Specifications

Type* Setter trolley 16 Setter trolley 17
Number of setter trays* > 256 > 272

* Trays and trolleys are not included

Number of incubation sections > 2 Number of temperature sensors > 2

Height/width/depth~(mm) > 2459~(+300~for~motor)~/~2293~/~4938~(+72)

Number of setter trolleys > 8

Heating > Electrical heating (optional integrated heating)

Cooling > Water cooling system with 34 vertical, parallel coils in each incubation section

Ventilation > Vortex™ air pump system in each incubation section

Set points per section > Separate temperature setpoints for each 4 trolley-section of up to 22,032 eggs

Incubator control > SmartTouch™ user interface



Bovendorpsstraat 11 7038 CH Zeddam The Netherlands

Phone +31 314 659 111 info@pasreform.com www.pasreform.com