Washing and waste handling |



Pas Reform Tipper unit

To automatically empty hatcher baskets





Tipper unit

Benefits

By turning the hatcher basket 180 degrees, the tipper unit's highly efficient mechanical turning mechanism optimises the disposal of hatcher basket waste. Easy to run, operator friendly and easily maintained, the hatcher basket tipper also delivers high reliability and conserves floor space, with low noise and vibration levels. Both the turning mechanism and the hatcher basket transport belt are located in a sealed stainless steel housing, to retain the majority of dust inside the machine. Suitable for connection to various waste transport systems for the hygienic discharge of residue, the tipper is constructed of stainless steel and easily cleaned with a high pressure washer.

How it works

- With a supply and discharge conveyor, the hatcher basket tipper is situated between the chick take-off system and the hatcher basket washing machine
- The system empties the basket by turning it 180° and tipping its contents into a funnel
- In its upside down position, the hatcher basket is then transported automatically into the hatcher basket washer to be thoroughly cleaned for re-use
- The transport belts prevent any used hatching paper from falling into the funnel.
 Instead it is deposited in a waste container behind the tipper unit

Related products

- ▶ SmartBasket™
- Manual chick separator
- ► Hatcher basket washer
- Macerator
- Vacuum waste system

Technical Specifications

Capacity > Up to 750 hatcher baskets per hour

Material > Durable stainless steel AISI304, easy to clean for maximum hygiene

Dimensions (LxW) > 1500 x 1500 mm (excl. conveyors)

> 3500 x 5550 mm (incl. conveyors)

Height > 2600 mm

Including > Inclining, easy maintainable infeed conveyor and discharge conveyor



Bovendorpsstraat 11 7038 CH Zeddam The Netherlands

Phone +31 314 659 111 info@pasreform.com www.pasreform.com